



HP V1700 Switch Series

Data sheet

Product overview

The HP V1700 Switch Series consists of two 10/100 fanless, Web-managed switches that are ideal for open offices that require silent operation or businesses making the transition from unmanaged to managed networks. The HP V1700-24 Switch is a 24-port switch with 22 10/100 ports plus two dual-personality ports. The HP V1700-8 Switch is a small-form-factor switch with seven 10/100 ports and one 10/100/1000 port. The HP V1700 Switch Series enables increased network capabilities without added complexity.

Key features

- Web-managed Layer 2 10/100 switch
- 8- and 24-port models
- Fanless switch for silent operation
- Two dual-personality mini-GBIC slots (J9080A)
- Industry-leading warranty



Features and benefits

Quality of Service (QoS)

- **IEEE 802.1p prioritization:** delivers data to devices by honoring the priority and type of traffic
- **Broadcast control:** allows limitation of broadcast traffic rate to cut down on unwanted broadcast traffic on the network

Resiliency and high availability

- **IEEE 802.3ad Link Aggregation Control Protocol (LACP):** provides link-level redundancy; support for up to 4 trunks, with up to 7 links (ports) per trunk on the HP V1700-8 Switch, and support for 12 trunks, with up to 8 links (ports) per trunk on the HP V1700-24 Switch.

Manageability

- **Intuitive Web interface:** enables simple management via an easy-to-use Web browser interface for switch configuration, monitoring, and administration
- **Integration with HP PCM:** enables discovery and mapping via HP PCM, available as a free download from the Web
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** automated device discovery protocol provides easy mapping using network management applications

Layer 2 switching

- **VLAN support and tagging:** support up to 64 port-based VLANs and dynamic configuration of IEEE 802.1Q VLAN tagging, providing security between workgroups

Security

- **Management password:** provides security so that only authorized access to the Web browser interface is allowed

Monitor and diagnostics

- **Port mirroring:** enables traffic on a port to be simultaneously sent to a network analyzer for monitoring

Ease of use

- **Comprehensive LED display with per-port indicators:** provides an at-a-glance view of status, activity, speed, and full-duplex operation
- **IEEE Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports

Flexibility

- **Small form factor:** ideal for desktop use; is space efficient for deployment flexibility (V1700-8 Switch only)
- **Designed with no fan:** enables quiet operation for deployment in open spaces

Warranty and support

- **Lifetime warranty:** for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)*
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; refer to www.hp.com/networking/warranty for details on the support provided and the period during which support is available
- **Software releases:** refer to www.hp.com/networking/warranty for details on the software releases provided and the period during which software releases are available for your product(s)

*Hardware warranty replacement for as long as you own the product, with next business day advance replacement (available in most countries) with a five-year hardware warranty replacement for the disk drive included with HP AllianceONE Services z1 Module, HP Threat Management Services z1 Module, HP PCM+ Agent with AllianceONE Services z1 Module, and HP E-MSM765 z1 Mobility Controller. For details, refer to the HP Software License, Warranty, and Support booklet at www.hp.com/networking/warranty.

HP V1700 Switch Series

Specifications



HP V1700-24 Switch (J9080A)



HP V1700-8 Switch (J9079A)

Ports	22 auto-sensing 10/100 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Media Type: Auto-MDIX; Duplex: half or full 2 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) or an open mini-GBIC slot (for use with mini-GBIC transceivers)	7 auto-sensing 10/100 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Media Type: Auto-MDIX; Duplex: half or full 1 auto-sensing 10/100/1000 port (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab Type 1000Base-T); Media Type: Auto-MDIX; Duplex: 10Base-T/100Base-TX: half or full; 1000Base-T: full only
Physical characteristics		
Dimensions	6.74(d) x 17.42(w) x 1.73(h) in. (17.12 x 44.25 x 4.39 cm) (1U height)	4.58(d) x 7.73(w) x 1.73(h) in. (11.63 x 19.63 x 4.39 cm) (1U height)
Weight	4.38 lb. (1.99 kg)	1.19 lb. (0.54 kg)
Memory and processor	2 MB flash, 2 MB RAM/ROM capacity; packet buffer size: 500 KB	1 MB flash, 1 MB RAM/ROM capacity; packet buffer size: 144 KB
Mounting	Mounts in an EIA-standard 19-in. telco racks (hardware included)	Horizontal surface mounting only
Performance		
100 Mb Latency	< 4.7 μ s (64-byte packets)	< 3.9 μ s (64-byte packets)
1000 Mb Latency	< 3.0 μ s (64-byte packets)	< 2.1 μ s (64-byte packets)
Throughput	up to 6.2 million pps (64-byte packets)	up to 2.0 million pps (64-byte packets)
Switching capacity	8.4 Gbps	3.4 Gbps
MAC address table size	8,000 entries	8,000 entries
Environment		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	15% to 95% @ 104°F (40°C), non-condensing	15% to 95% @ 104°F (40°C), non-condensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/Storage relative humidity	10% to 90% @ 149°F (65°C), non-condensing	10% to 90% @ 149°F (65°C), non-condensing
Altitude	up to 10,000 ft. (3 km)	up to 10,000 ft. (3 km)
Acoustic	Power: 0 dB No Fan	Power: 0 dB No Fan
Electrical characteristics		
Maximum heat dissipation	82 BTU/hr (87 kJ/hr)	61 BTU/hr (64 kJ/hr)
Voltage	100-127 / 200-240 VAC	100-127 / 200-240 VAC
Current	0.7 / 0.4 A	1.0 / 0.8 A
Maximum power rating	24 W	18 W
Frequency	50 / 60 Hz	50 / 60 Hz
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adapter part number ordered. Please select the correct power adapter country option.
Safety	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950
Emissions	FCC Rules Part 15, Subpart B Class A; EN 55022; VCCI; ICES-003 (Canada)	FCC Rules Part 15, Subpart B Class A; EN 55022; VCCI; ICES-003 (Canada)
Immunity		
EN	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2	IEC 61000-4-2
Radiated	IEC 61000-4-3	IEC 61000-4-3
EFT/Burst	IEC 61000-4-4	IEC 61000-4-4
Surge	IEC 61000-4-5	IEC 61000-4-5
Conducted	IEC 61000-4-6	IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8	IEC 61000-4-8
Voltage dips and interruptions	IEC 61000-4-11	IEC 61000-4-11
Harmonics	IEC 61000-3-2	IEC 61000-3-2
Flicker	IEC 61000-3-3	IEC 61000-3-3
Management	Web browser	Web browser
Notes	Use only supported genuine HP mini-GBICs with your switch. Use only supported genuine ProCurve mini-GBICs with your switch.	Use only supported genuine HP mini-GBICs with your switch.

HP V1700 Switch Series

Specifications (continued)

	HP V1700-24 Switch (J9080A)	HP V1700-8 Switch (J9079A)
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UF803E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UF804E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UF806E) 3-year, 24x7 SW phone support, software updates (UF805E) Installation with minimum configuration, system-based pricing (U4826E) Installation with HP-provided configuration, system-based pricing (U4830E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR832E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR833E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR834E) 4-year, 24x7 SW phone support, software updates (UR835E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR836E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UR837E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR838E) 5-year, 24x7 SW phone support, software updates (UR839E) 3 Yr 6 hr Call-to-Repair Onsite (UW395E) 4 Yr 6 hr Call-to-Repair Onsite (UW396E) 5 Yr 6 hr Call-to-Repair Onsite (UW397E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UF799E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UF800E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UF802E) 3-year, 24x7 SW phone support, software updates (UF801E) Installation with minimum configuration, system-based pricing (U4826E) Installation with HP-provided configuration, system-based pricing (U4830E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR824E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR825E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR826E) 4-year, 24x7 SW phone support, software updates (UR827E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR828E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UR829E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR830E) 5-year, 24x7 SW phone support, software updates (UR831E) 3 Yr 6 hr Call-to-Repair Onsite (UW392E) 4 Yr 6 hr Call-to-Repair Onsite (UW393E) 5 Yr 6 hr Call-to-Repair Onsite (UW394E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
Standards and protocols (applies to all products in series)	<p>General protocols IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3x Flow Control</p>	<p>RFC 1534 DHCP/BOOTP Interoperation</p> <p>Network management IEEE 802.1AB Link Layer Discovery Protocol (LLDP)</p>

HP V1700 Switch Series accessories

Cables

NEW HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

NEW HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)

NEW HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)

NEW HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)

NEW HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)

NEW HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)

NEW HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)

NEW HP 0.5 m PremierFlex OM3+ LC/LC Optical Cable (BK837A)

HP V1700-24 Switch (J9080A)

HP X121 1G SFP LC LH Transceiver (J4860C)

HP X121 1G SFP LC SX Transceiver (J4858C)

HP X121 1G SFP LC LX Transceiver (J4859C)

HP X122 1G SFP LC BX-D Transceiver (J9142B)

HP X122 1G SFP LC BX-U Transceiver (J9143B)

To learn more, visit www.hp.com/networking

© Copyright 2007, 2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA1-0121ENW, Created January 2007; Updated September 2010, Rev. 2

